



N.V. DOTHÉE S.A.

# RD-REPAIR FIBER

Repairing product for roofs

## DESCRIPTION OF THE PRODUCT

USE	Solventborne onecomponent repairing and waterproofing product for roofs. Based on acrylic polymers and fibres. Very appropriate for the immediate repair of leaks in roofs, pipes, and gutters ... This product can be applied by any weather.
FEATURES	Extreme elasticity - Excellent water tightness.
SUBSTRATES	Suits to most substrates, such as asphalt, bitumen, polyester or zinc. The product can't be applied on new concrete.
SYSTEM:	Direct application of 1 coat of RD-REPAIR FIBER on the substrate.

## APPLICATION INSTRUCTIONS

PREPARATION OF THE SUBSTRATE:	The substrate has to be cleaned carefully, with a hard brush and, after that, with a wet sponge.
APPLICATION CONDITIONS	Can be applied by rain or frost.
APPLICATION MEANS	Brush or plasterness.
DILUTION :	RD-THINNER RR
CLEANING OF TOOLS:	RD-THINNER RR
CONSUMPTION :	1 to 2 L/m <sup>2</sup> .
PARTICULARITIES	Clean the tools immediately after use.

**TECHNICAL DATA**

FINISH:	Satin gloss
COLOURS :	Grey
SOLIDS CONTENT :	In weight: ca. 55% In volume: ca. 50%
VOC CONTENT :	Max 420g/L
DENSITY:	Ca. 1.06
FLASH POINT :	> 21°C
VISCOSITY:	150 – 200 P (Brookfield – 20 Rpm)
DRYING TIME:	24 hours
PACKING:	1 L – 5 L – 20L
STORAGE STABILITY:	12 months: keep away from heat.

**SAFETY DATA**

- R 10 Flammable
- R 66 Repeated exposure may cause skin dryness or cracking.
- S 02 Keep out of reach of children
- S 23 Do not breathe vapour/spray
- S 46 If swallowed, seek medical advice immediately and show this container or label.
- S 51 Use only in well-ventilated areas.

The safety data sheet is available on request.

These specifications are given for information. Since the manufacturer is not able to check the right application of the products, he cannot accept any responsibility for it. This technical data sheet replaces all previous editions.