



N.V. DOTHÉE S.A.

# RD-ELASTOFRIGO

Waterproofing for cold stores

## DESCRIPTION OF THE PRODUCT

USE	Waterborne onecomponent waterproofing product for the recovering of walls and roofs of cold stores. Based on acrylic dispersion.
FEATURES	Formation of an elastic and waterproofing film - Gas and vapour tight - Fungicide.
SUBSTRATES	Several mineral and bituminous substrates.
SYSTEM:	<p>Slightly porous substrates: 2 coats directly on the substrate, without primer.</p> <p>Very porous substrates:</p> <ul style="list-style-type: none"> <li>• Primer: 1 coat of impregnation RD-UNIFIX.</li> <li>• Finishing: 2 coats of RD-ELASTOFRIGO.</li> </ul>

## APPLICATION INSTRUCTIONS

PREPARATION OF THE SUBSTRATE:	The substrate has to be clean, dry, and free of dust.
APPLICATION CONDITIONS	Ambient temperature: > 5°C R.H.: max. 80%
APPLICATION MEANS	Brush, roller or airless (nozzle: 018–023).
DILUTION :	Water (only for use of airless)
CLEANING OF TOOLS:	Water
CONSUMPTION :	Ca. 1 Kg/m <sup>2</sup> per coat.
PARTICULARITIES	Mix well before use.



**TECHNICAL DATA**

FINISH:	Satin flat.
COLOURS :	White
SOLIDS CONTENT :	In weight: ca. 71 % In volume: ca. 58 %
VOC CONTENT:	Max 1g/L
DENSITY:	Ca. 1.45
FLASH POINT :	Not flammable.
VISCOSITY:	150 – 200 P (Brookfield 20 Rpm)
DRYING TIME:	On touch: 4 hours Recoatible: 24 hours.
PACKING:	5 Kg – 25 Kg
STORAGE STABILITY:	12 months, keep away from frost.

**SAFETY DATA**

The safety data sheet is available on request.

These specifications are given for information. Since the manufacturer is not able to check the right application of the products, he cannot accept any responsibility for it. This technical data sheet replaces all previous editions.