

RD-ELASTOVAR

DESCRIPTION OF THE PRODUCT

USE	Waterborne onecomponent satin varnish, for indoor and outdoor use. Based on acrylic resin. Is able to bridge small cracks due to its elasticity.
FEATURES	Elastic system - Good resistance against weathering - No yellowing.
SUBSTRATES	Colourless protection for concrete, bricks and tiles. For outside walls : application only if there is a space between 2 cavity walls.
SYSTEM:	On porous substrates: <ul style="list-style-type: none">• Primer: 1 coat of diluted RD-ELASTOVAR .• Topcoat: 1 coat of RD-ELASTOVAR . On not porous substrates: <ul style="list-style-type: none">• Primer: 1 coat of RD-ELASTOVAR.• Topcoat: 1 coat of RD-ELASTOVAR.

APPLICATION INSTRUCTIONS

PREPARATION OF THE SUBSTRATE:	The substrate has to be dry, degreased and free of dust.
APPLICATION CONDITIONS	Outdoor: by dry weather. Ambient temperature: > 5°C R.H.: max. 90%
APPLICATION MEANS	Brush, roller or airless (nozzle: 013-015).
DILUTION :	Water.
CLEANING OF TOOLS:	Water.
CONSUMPTION :	Ca. 10m ² /L per coat.
PARTICULARITIES	Mix well before use.

TECHNICAL DATA

FINISH:	Satin.
COLOURS :	Colourless.
SOLIDS CONTENT :	In weight : ca. 34 % In volume : ca. 30 %
VOC CONTENT:	Max 55 g/L
DENSITY:	Ca. 1.05
FLASH POINT :	Not flammable.
VISCOSITY:	20 – 40 P (Brookfield 20 Rpm).
DRYING TIME:	On touch: 1 hour Recoatable: 4 hours.
PACKING:	1 L – 2.5 L – 20 L
STORAGE STABILITY:	12 months, keep away from heat.

SAFETY DATA

The safety data sheet is available on request.

These specifications are given for information. Since the manufacturer is not able to check the right application of the products, he cannot accept any responsibility for it. This technical data sheet replaces all previous editions.