



N.V. DOTHÉE S.A.

BALCONIES & TERRACES





N.V. DOTHÉE S.A.

Balconies & Terraces

Waterproofing system suitable for all balconies or terraces, consisting of:

- Cement tiles
- Glazed or baked tiles
- Pure concrete
- Asphalt-tarmac etc.

To apply a walkable, protective and aesthetic waterproof coating system.

Normal method:

- Cleaning according to the state of the art.
- Ensuring a stable substrate and operational drains (gutters)
- If it concerns a very porous surface, than in a impregnation coat of RD-Unifix is indicated.
- Consumption 4 to 6M2 / L

Apply on a dry and clean substrate a coat of RD-ELASTODECK, in the wet coat stick-RD-ROOF-FLEECE .

Let dry.

Application of a second coat of RD-ELASTODECK in order to completely recover the fleece.

Consumption: Approximately 1.5 kg/m²-RD-ELASTODECK depending on the condition of the substrate.

On a stable concrete substrate, where only an aesthetic finish is required generally one coat of RD-ELASTODECK at the rate of 1 kg/m² is sufficient.

Topcoat:

After drying, application of a topcoat: RD-MONOFLOOR.

Consumption: 4 to 6 M2 / L

RD-MONOFLOOR has a slight anti-slip structure, walkable and suitable for normal pedestrian traffic and mechanical resistant against furniture.

